

10/538294
Rec'd PTO 10 JUN 2005

WO 2004/056627 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DESCRIPTION

Technical sector of the invention

The present invention relates to a washer fluid squirt device for motor vehicle windscreen washer jets.

Background to the invention

Many embodiments of washer fluid squirt devices for motor vehicle windscreens are known. Essentially, said devices are comprised of a jet body and a squirt body, capable of being mutually coupled, wherein the jet body is equipped with means for its mounting onto the vehicle bodywork and means for the connection of a washer fluid pipe from a tank, and the squirt body is equipped with means for squirting washer fluid onto the windscreen and means for allowing said squirt to be directed in order to optimise the action of the wiper blades.

The patent ES P 200100234, by the same applicant, discloses a washer fluid squirt device which, in essence, comprises a jet body and a unit for a fan-shaped squirt of washer fluid, consisting of a first squirt body and a second squirt body, capable of being mutually coupled and configuring two equal conduits of washer fluid which originate in an inlet chamber and converge in an outlet chamber.

The patent FR 2 803 542 discloses a water jet for motor vehicle windscreen washer fluid, essentially comprised of a jet body and a body for a fan-shaped squirt of washer fluid, equipped with a rectangular section conduit, wherein there is a longitudinal centred rib, said conduit originating in a transversally cylindrical inlet chamber.

The patent 2 726 204 discloses a jet for cleaning motor vehicle windscreens which is essentially comprised of a jet body and a body for a fan-shaped squirt of washer fluid, equipped with a circular section conduit, the outer end of which has a transversally arranged V-shaped outlet aperture.

Explanation of the invention

The washer fluid squirt device for motor vehicle windscreen washer jets object of the invention, is comprised of a jet body and a body for a fan-shaped squirt of washer fluid provided with a squirting orifice and coupled to the jet body, in such a way that it can be rotated around its longitudinal axis.

The device of the invention is characterised in that the squirting orifice comprises four conduit portions which are consecutively connected without

- 2 -

interruption, thus defining a conduit axis and in such a way that its longitudinal section is symmetrical with regard to a theoretical main transverse plane, of which the first portion, which is the innermost one, is conical and in progressively decreasing section in the flow direction of the washer fluid; the second portion forms
5 a spherical cap of decreasing section in the flow direction of the washer fluid; the third portion is in rectangular cross-section and in progressively increasing section in the flow direction of the washer fluid and when connecting with the second portion configures a rectangular window whose end sides are situated inwardly with regard to the tangency determined by the connection of the first portion with the second
10 portion; and the fourth portion is in rectangular cross-section in decreasing section in the flow direction of the washer fluid, which configures without interruption, a convex outlet edge for the washer fluid and wherein the squirt body is equipped with a lateral squirting groove, perpendicularly arranged as regards the conduit axis of the squirting orifice, which surrounds the exit edge of the squirting orifice and the bottom
15 part thereof is below the level corresponding to the connection of the third portion with the fourth portion of the squirting orifice.

It is also characteristic of the device of the invention that the lateral squirting groove has a cross-section whose outline comprises a first concave portion that connects tangentially with the convex exit edge of the squirting orifice and a second
20 straight portion that connects tangentially with the first concave portion, forming an outwardly directed angularity.

The previously described features of the device of the invention provide solutions to problems which the known embodiments of squirt devices, such as the aforementioned create, most prominent among said problems being the uniform
25 distribution of washer fluid in the arc shaped by the fan-shaped squirt; the plugging of the sides of the squirt aperture, caused by low temperatures, resulting in the washer fluid being squirted onto one place on the windscreen as a single jet; and high production costs. The characteristics of the device of the invention provide the advantages which are set out in detail below. The fan-shaped squirting of washer
30 fluid is done by concentrating a greater amount of washer fluid in the outer areas of the fan, thus enhancing the driver's vision during the spraying of the windscreen, unlike the known embodiments wherein the fluid distribution is uniform throughout the entire fan-shaped squirt; the washer fluid is squirted by means of an outlet aperture which is large enough to ensure a fan-shaped squirt at low temperatures,
35 unlike the known embodiments, wherein the outlet aperture leads to the plugging of its lateral areas, and thus results in the loss of the fan-shaped squirt of liquid; and,

- 3 -

the fact that the squirt body is made up of a single part reduces production costs in relation to those embodiments requiring two or more parts in order to attain the fan-shaped squirting of washer fluid.

5 Brief description of the drawings

Illustrated in the attached drawings, by way of non-limiting example, is a form of embodiment of the washer fluid squirt device for motor vehicle windscreen washer jets object of the invention. In said drawings:

- Fig. 1 is a diagrammatic view of the squirt device of the invention;
10 Figs. 2, 3 and 4 are respective side views of the squirt body of the squirt device of the invention;
Fig. 5 is the view corresponding to section V-V of Fig.2; and
Fig. 6 is the view corresponding to section VI-VI of Fig. 2.

15 Detailed description of the drawings

In Fig. 1, the washer fluid squirt device 1 for motor vehicle windscreen washer jets object of the invention is represented and which, as an embodiment example, is described below. The squirt device 1 essentially comprises a jet body 2, which is basically parallelepiped and adapted to each specific application and an essentially cylindrical-shaped body 3 for a fan-shaped squirting of washer fluid, both
20 being mutually coupled. The jet body 2 is provided with a slot 4, adapted to snugly receive the squirt body 3 and in such a way that the latter may be rotated around its longitudinal axis, with means for fixing to the vehicle bodywork, not shown, and with means for connecting a washer fluid pipe, which are also not shown, as well as a
25 conduit 5, represented by dashes, which connects said washer fluid pipe hydraulically with the slot 4.

In Figs. 2, 3 and 4, it can be appreciated that the squirt body 3 is provided with positioning means with regard to the jet body 2, which comprise a protuberance 6 at one of its ends and a groove 7 at the other end, the protuberance 6 being
30 adapted for housing in a corresponding cavity, not shown, of the slot 4 of the jet body 2, intended to limit the rotation of the squirt body 3 around its longitudinal axis, whereas the groove 7 is adapted for receiving a tool, such as the blade end of a screwdriver, enabling the user to rotate the squirt body 3, thus determining the area in which the washer fluid squirted in a fan-shape 8 reaches the vehicle windscreen.

35 With reference to Figs. 5 and 6, it can be appreciated that the squirt body 3 is equipped with a squirting orifice 9, arranged transversally and in such a way that,

- 4 -

as Fig. 1 shows, it remains facing the conduit 5 that connects hydraulically with said washer fluid pipe. Fig. 5 shows in detail that the squirting orifice 9 comprises four well-defined conduit portions, which are connected consecutively and whose longitudinal section is symmetrical with regard to a theoretical main transverse plane of the squirt body 3. The first portion 10, that which is facing the conduit 5 of the jet body 2, is conical and has a progressively decreasing section in the flow direction of the washer fluid; the second portion 11 forms a spherical cap with decreasing section in the flow direction of the washer fluid; the third portion 12 has a rectangular cross-section and progressively increasing section in the flow direction of the washer fluid, configuring, in its connection with the second portion 11, a rectangular window 13, represented in Figs. 2 and 4, whose end sides 14, represented in Fig. 6, are situated inwardly with regard to the tangency determined by the connection of the first portion 10 with the second portion 11, indicated in Fig. 6 by means of a dashed line; and the fourth portion 15 has a rectangular cross-section in decreasing section in the flow direction of the washer fluid, this fourth portion 15 determining a large outwardly convex outlet edge 16 which, in this embodiment example of the device of the invention, confines itself to a circumferential edge over a spherical cap 17 which configures the lateral surface of the squirt body 3, represented in Figs. 3 and 4.

The squirt body 3 has a lateral squirting groove 18, shown in section in Fig. 5, perpendicularly arranged with regard to the longitudinal axis of the squirting orifice 9 and which surrounds the outlet edge 16, the squirt groove 18 having a cross-section whose outline comprises a first concave portion 19 which connects tangentially at one end with the convex edge 16 of the squirting orifice 9, and by one end connects with a second straight portion 20 that forms an outwardly directed angularity, all adapted so that the bottom part of the lateral squirt groove 18 is situated below the level corresponding to the connection of the third portion 12 with the fourth portion 15 of the squirting orifice 9.

The fan-shaped squirting of the washer fluid by the squirting device of the invention is represented in Fig. 1, wherein it can firstly be appreciated that the squirting of washer fluid onto the vehicle windscreen is symmetrical with regard to a vertical plane Y-Y, and secondly, that it results in a greater concentration of washer fluid at the ends of the fan-shaped squirt, and this, as has been pointed out earlier, enhances the driver's vision during the spraying of the windscreen.

- 5 -

CLAIMS

1. Washer fluid squirt device for motor vehicle windscreen washer jets object of the invention, comprised of a jet body (2) and a body (3) for a fan-shaped squirt of washer fluid equipped with a squirting orifice (9) and coupled to the jet body (2), in such a way that it can be rotated around its longitudinal axis, characterised in that the squirting orifice (9) comprises four conduit portions which are consecutively connected without interruption, thus defining a conduit axis and in such a way that its longitudinal section is symmetrical with regard to a theoretical main transverse plane, of which the first portion (10), which is the innermost one, is conical and in progressively decreasing section in the flow direction of the washer fluid; the second portion (11) forms a spherical cap in decreasing section in the flow direction of the washer fluid; the third portion (12) is in rectangular cross-section and in progressively increasing section in the flow direction of the washer fluid and when connecting with the second portion (11) configures a rectangular window (13) whose end sides (14) are situated inwardly with regard to the tangency determined by the connection of the first portion (10) with the second portion (11); and the fourth portion (15) is in rectangular cross-section in decreasing section in the flow direction of the washer fluid, which configures without interruption a convex exit edge (16) of the washer fluid and in that the squirt body (3) is provided with a lateral squirting groove (18) perpendicularly arranged as regards the conduit axis of the squirting orifice (9), which surrounds the exit edge (16) of the squirting orifice (9) and the bottom part of which is below the level corresponding to the connection of the third portion (12) with the fourth portion (15) of the squirting orifice (9).

25

2. Squirt device according to claim 1, characterised in that the lateral squirting groove (18) has a cross-section whose outline comprises a first concave portion (19) that connects tangentially with the convex exit edge (16) of the squirting orifice (9) and a second straight portion (20) that connects tangentially with the first concave portion (19), forming an outwardly orientated angularity.

30

1 / 2




FIG. 1




FIG. 2




FIG. 3




FIG. 4

2 / 2




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/13301

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B60S1/52 B05B1/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60S B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 803 542 A (RENAULT) 13 July 2001 (2001-07-13) cited in the application page 4, line 15 -page 6, line 10 figure 4	1
A	FR 2 726 204 A (SEIM IND) 3 May 1996 (1996-05-03) cited in the application page 6, line 4 - line 24 figures 4,5	1
A	WO 02/060589 A (MOTA LOPEZ MIGUEL ;ELVIRA PERALTA JUAN JOSE (ES); FICO TRANSPAR SA) 8 August 2002 (2002-08-08) page 2, line 6 - line 24 page 5, line 10 - line 25 figures	1
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *G* document member of the same patent family

Date of the actual completion of the international search

27 April 2004

Date of mailing of the international search report

04/05/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Roldán, J

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/13301

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 062 452 A (BOSCH GMBH ROBERT) 28 May 1981 (1981-05-28) page 1, line 115 -page 2, line 19 figures 2-4 ----	1
A	US 5 975 431 A (HARITA YASUHIRO ET AL) 2 November 1999 (1999-11-02) column 1, line 42 - line 52 column 4, line 1 - line 29 figures ----	1
A	US 6 082 636 A (IWAZAKI KOJI ET AL) 4 July 2000 (2000-07-04) the whole document ----	1
A	WO 02/26537 A (KONDO TAKATOSHI ;MITSUBA CORP (JP)) 4 April 2002 (2002-04-04) the whole document ----	1
A	US 4 865 059 A (LELEVE JOEL) 12 September 1989 (1989-09-12) column 3, line 40 - line 60 figures -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/13301

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2803542	A	13-07-2001	FR 2803542 A1	13-07-2001
FR 2726204	A	03-05-1996	FR 2726204 A1	03-05-1996
WO 02060589	A	08-08-2002	ES 2200620 A1 WO 02060589 A1	01-03-2004 08-08-2002
GB 2062452	A	28-05-1981	DE 2945084 A1 BE 886094 A1 FR 2469327 A1	14-05-1981 02-03-1981 22-05-1981
US 5975431	A	02-11-1999	JP 3155230 B2 JP 11034812 A JP 3157747 B2 JP 11034813 A CA 2229236 A1 DE 19753446 A1 JP 2001171488 A	09-04-2001 09-02-1999 16-04-2001 09-02-1999 21-11-1998 26-11-1998 26-06-2001
US 6082636	A	04-07-2000	JP 3076549 B2 JP 2000052939 A CA 2279656 A1	14-08-2000 22-02-2000 06-02-2000
WO 0226537	A	04-04-2002	JP 2002096718 A EP 1359074 A1 WO 0226537 A1 US 2003178506 A1	02-04-2002 05-11-2003 04-04-2002 25-09-2003
US 4865059	A	12-09-1989	FR 2619066 A1 DE 3862450 D1 EP 0306378 A1 JP 1067450 A JP 2673204 B2	10-02-1989 23-05-1991 08-03-1989 14-03-1989 05-11-1997